

Distortion equation of motion in linear incompatible elastodynamics

R. WOJNAR

Polish Academy of Sciences

Institute of Fundamental Technological Research

Świętokrzyska 21, 00-049 Warszawa, Poland

rwojnar@ippt.gov.pl

THE PAPER DEALS with an initial-boundary value problem of linear incompatible elastodynamics, based on Kosevich' theory of continuously distributed defects due to prescribed plastic fields, [1, 2, 3]. In analogy to a stress formulation of linear incompatible elastodynamics with continuously distributed defects, [4], a distortion formulation is proposed. In such a formulation the tensorial initial-boundary value problem for an unknown asymmetric tensor field is to be solved. A solution to the problem generates the associated stress and rotation fields.

1. Introduction

THE STRESS FORMULATION of linear elastodynamics is a counterpart of the displacement formulation (cf. IGNACZAK [5, 6]). The stress formulation was applied to a dislocation theory by IGNACZAK and RAO in their fundamental work [4]. In the present paper we give the formulation of a problem of linear elastodynamics with defects in terms of an asymmetric distortion tensor field, and prove an appropriate uniqueness theorem. Also, we show that by a symmetrization, the problem and uniqueness theorem reduce to those of a pure stress formulation of elastodynamics with continuously distributed defects, cf. [4]. In addition, we use a solution to the distortion initial-boundary value problem to obtain a dislocation density formula from [4], see Eq.(2.11) in [4].

If the displacement field of a solid with defects is described by a vector u_i , ($u_i = u_i^T$, where u_i^T is the total displacement introduced in [4]), then the distortion tensor w_{ij} is defined as, cf. LANDAU and LIFSHITZ [2],

$$(1.1) \quad w_{ij} = u_{j,i}.$$

Of course, in general tensor w_{ij} is not symmetric, i.e. $w_{ij} \neq w_{ji}$.

In the defect theory, the integral of w_{ij} along a contour L which encloses the dislocation line D is equal to Burger's vector \tilde{b}_i , cf. Fig. 1.




FIG. 1. The contour of integration L enclosing the dislocation line D . The direction of the contour integration and the chosen direction of the tangent vector τ to the line D are related by the corkscrew rule, after [2]. Vector \mathbf{n} is normal to the dislocation loop surface and vector ξ is a radius vector taken from the line D in the plane perpendicular to the vector τ .

Therefore, the following relation holds true:

$$(1.2) \quad \oint_L w_{ik} n_i dl = -\tilde{b}_k.$$

Using Stokes' theorem, this integral relation can be written in a differential form

$$(1.3) \quad \varepsilon_{imn} w_{nk,m} = -\tau_i \tilde{b}_k \delta(\xi),$$

where ε_{imn} is the permutation symbol (the antisymmetric unit tensor), vector τ_i denotes the unit tangent to the dislocation line D , and ξ is the two-dimensional position vector taken from the dislocation line in the plane perpendicular to the vector τ_i at the point considered; and $\delta = \delta(\xi)$ represents the Dirac delta function, cf. also the Appendix.

If we introduce, after [2], the dislocation density tensor ρ_{ik} , defined as

$$(1.4) \quad \int_{S_L} \rho_{ik} df_i = \tilde{b}_k$$

where integration is performed over a surface S_L spanned by the contour L , we write instead of relation (1.3), the following equality

$$(1.5) \quad \varepsilon_{ijm} w_{mk,j} = -\rho_{ik}.$$

Hence, tensor ρ_{ik} satisfies the condition

$$(1.6) \quad \rho_{ik,i} = 0$$

which for a single dislocation expresses the conservation of the Burgers vector along the dislocation line.

For convenience, and to make comparisons with [4] easier, we use the notation adopted in [4]

$$(1.7) \quad \alpha_{ik} \equiv -\rho_{ik}.$$

Then, Eqs. (1.5) and (1.6) take the forms

$$(1.5)' \quad \varepsilon_{ijm} w_{mk,j} = \alpha_{ik}$$

and

$$(1.6)' \quad \alpha_{ik,i} = 0.$$

Equations (1.5) or (1.5)' hold true both for dislocations which are at rest and those in motion, if only the elastic displacements are taken into account. However, the motion of a dislocation can be related to a plastic deformation, as well. An exhaustive discussion of the elastodynamic theory of defects in which plastic deformations are prescribed, and the defects are characterized in terms of a symmetric stress tensor field, is presented in [4]. In the following, we present a ramification of the results obtained in [4] in which an asymmetric distortion tensor field plays a central role.

A total distortion tensor w_{ij}^T , denoted in [2] by W_{ij} , is postulated in the form

$$(1.8) \quad w_{ij}^T = w_{ij}^E + w_{ij}^P,$$

where w_{ij}^E and w_{ij}^P represent the elastic and plastic parts of the distortion, respectively,

$$(1.9) \quad w_{ij}^T = u_{j,i}$$

and neither elastic nor plastic part of decomposition (1.8) are obtained by the gradient of a vector field. Clearly, relations (1.1) to (1.6) are valid for $w_{ij} \equiv w_{ij}^E$ and $w_{ij}^P \equiv 0$.

If, in addition, it is postulated that (1.5)' is satisfied by the elastic part w_{ij}^E only, i.e.

$$(1.10) \quad \varepsilon_{ijm} w_{mk,j}^E = \alpha_{ik}$$

then, by (1.8) and (1.9), we obtain

$$(1.11) \quad \varepsilon_{ijm} w_{mk,j}^P = -\alpha_{ik}.$$

The total deformation tensor e_{ij}^T , and elastic and plastic strain tensors e_{ij}^E and e_{ij}^P are defined in terms of w_{ij}^T , w_{ij}^E and w_{ij}^P by {cf. [4], Eqs. (2.1) – (2.2)}

$$(1.12) \quad 2e_{ij}^T = w_{ij}^T + w_{ji}^T,$$

$$(1.13) \quad 2e_{ij}^E = w_{ij}^E + w_{ji}^E (\equiv 2e_{ij}),$$

$$(1.14) \quad 2e_{ij}^P = w_{ij}^P + w_{ji}^P.$$

Other fields of the defect theory such as the dislocation moment density can be also defined in terms of the tensor w_{mn}^P , (cf. LANDAU and LIFSHITZ [2], KOSEVICH [3]).

2. Basic field equations and initial boundary value problem

Let a nonhomogeneous anisotropic linear elastic body, occupying a three-dimensional region B , be subject to a dynamic motion. Let the body forces be absent. Let the displacement be described by a vector u_i . Then the distortion tensor w_{ij}^T is defined as, cf. (1.9),

$$(2.1) \quad w_{ij}^T = u_{j,i}.$$

The relation between the strain tensor e_{ij}^T and the distortion tensor w_{ij}^T is given by (1.12), and the relation between the stress tensor s_{ij}^E and the strain tensor e_{ij}^T is given by the generalized Hooke's law, cf. SOKOLNIKOFF [7], NOWACKI [8],

$$(2.2) \quad s_{ij}^E = C_{ijmn} e_{mn}^E,$$

where C_{ijmn} is the elasticity tensor. The inverse relation reads

$$(2.3) \quad e_{ij}^E = K_{ijmn} s_{mn}^E,$$

where K_{ijmn} is the compliance tensor, *i.e.*:

$$C_{ijpq} K_{pqmn} = \delta_{i(m} \delta_{jn)} \quad \text{on } B$$

and δ_{ij} stands for Kronecker's symbol.

Thus, instead of (2.2) we can write

$$(2.4) \quad s_{ij}^E = C_{ijmn} w_{mn}^E$$

or taking into account (1.8), we get

$$(2.5) \quad s_{ij}^E = C_{ijmn} (w_{mn}^T - w_{mn}^P) (\equiv s_{ij}).$$

In Eqs. (2.2) – (2.5) the symmetry relations are postulated

$$(2.6) \quad C_{ijmn} = C_{jimn} = C_{ijnm} = C_{mnij}, \quad K_{ijmn} = K_{jimn} = K_{ijnm} = K_{mnij}.$$

The equation of motion takes the form

$$(2.7) \quad s_{ik,k}^E + b_i = \rho \ddot{u}_i,$$

where $\rho = \rho(\mathbf{x})$ and $\mathbf{b} = \mathbf{b}(\mathbf{x})$ denote the mass density and body force vector fields.

Finally, the density ρ and compliance K_{ijkl} satisfy the inequalities

$$(2.8) \quad \rho > 0, \quad K_{ijkl}\xi_{ij}\xi_{kl} > 0$$

for every tensor field $\xi_{ij}(\mathbf{x})$, $\mathbf{x} \in B$, not necessarily symmetric.

3. Distortion equation of motion

After differentiation of equation of motion (2.7) and use of definition of distortion (2.1), we get

$$(3.1) \quad (\rho^{-1}s_{ik,k}^E)_{,j} + (\rho^{-1}b_i)_{,j} = \ddot{w}_{ij}^T, \quad (\mathbf{x}, t) \in B \times [0, \infty)$$

or, by (2.5),

$$\left\{ \rho^{-1}[C_{ikmn}(w_{mn}^T - w_{mn}^P)]_{,k} \right\}_{,j} + (\rho^{-1}b_i)_{,j} = \ddot{w}_{ij}^T, \quad (\mathbf{x}, t) \in B \times [0, \infty)$$

or

$$(3.2) \quad [\rho^{-1}(C_{ikmn}w_{mn}^T)_{,k}]_{,j} + \hat{b}_{i,j} = \ddot{w}_{ij}^T, \quad (\mathbf{x}, t) \in B \times [0, \infty).$$

This is the distortion equation of elastodynamics we are to deal with. The term

$$(3.2a) \quad \hat{b}_i \equiv [b_i - (C_{ikmn}w_{mn}^P)_{,k}]/\rho$$

is to be considered as the given density of body forces distributed in a crystal, (cf. [2]).

The above field equation is subject to the initial conditions

$$(3.3) \quad w_{ij}^T(\mathbf{x}, 0) = w_{ij}^o(\mathbf{x}), \quad \dot{w}_{ij}^T(\mathbf{x}, 0) = \dot{w}_{ij}^o(\mathbf{x}) \quad \mathbf{x} \in B$$

and boundary conditions

$$\begin{aligned}
 (3.4) \quad & u_i^0(\mathbf{x}) + t\dot{u}_i(\mathbf{x}) + \rho^{-1}t * (C_{ikmn}w_{mn}^T)_{,k}(\mathbf{x}, t) = \mathcal{U}_i(\mathbf{x}, t) \\
 & \text{on } \partial B_{\mathcal{U}} \times [0, \infty), \\
 & (C_{ijmn}w_{mn}^T)n_j = \mathcal{F}_i(\mathbf{x}, t) \text{ on } \partial B_{\mathcal{F}} \times [0, \infty),
 \end{aligned}$$

where $\partial B_{\mathcal{U}} \cup \partial B_{\mathcal{F}} = \partial B$, $\partial B_{\mathcal{U}} \cap \partial B_{\mathcal{F}} = \emptyset$.

The fields $w_{ij}^0(\mathbf{x})$ and $\dot{w}_{ij}^0(\mathbf{x})$ are determined by the initial displacement field $u_i(\mathbf{x}, 0) = u_i^o(\mathbf{x})$ and the initial velocity field $\dot{u}_i(\mathbf{x}, 0) = \dot{u}_i^o(\mathbf{x})$ through the relations

$$w_{ij}^0(\mathbf{x}) = u_{j,i}^0(\mathbf{x}), \quad \dot{w}_{ij}^0(\mathbf{x}) = \dot{u}_{j,i}^o(\mathbf{x}) \quad \text{on } B.$$

Moreover, the field $\mathcal{U}_i(\mathbf{x}, t)$ is expressed by the boundary displacement $\hat{u}_i(\mathbf{x}, t)$, and the initial data $u_i^o(\mathbf{x})$ and $\dot{u}_i^o(\mathbf{x})$, through

$$\mathcal{U}_i(\mathbf{x}, t) = \hat{u}_i(\mathbf{x}, t) - t\dot{u}_i^o(\mathbf{x}) - u_i^o(\mathbf{x}).$$

Finally, the field $\mathcal{F}_i(\mathbf{x}, t)$ represents the surface traction.

THEOREM 1. (*Uniqueness theorem for a distortion initial-boundary value problem of elastodynamics with defects*).

The problem (3.2) – (3.4) has at most one solution.

P r o o f. It is sufficient to show that the problem (3.2) – (3.4) corresponding to homogeneous data has a zero solution only.

Introduce the notations

$$(a) \quad s_{ij} = C_{ijmn}w_{mn}^T$$

and

$$(b) \quad W_{ij} = w_{ij}^T.$$

Then, the homogenous counterparts to Eqs. (3.2) – (3.4) read

$$(3.2)' \quad (\rho^{-1}s_{ik,k})_{,j} = \ddot{W}_{ij}, \quad (\mathbf{x}, t) \in B \times [0, \infty)$$

$$(3.3)' \quad W_{ij}(\mathbf{x}, 0) = 0, \quad \dot{W}_{ij}(\mathbf{x}, 0) = 0, \quad \mathbf{x} \in B;$$

$$(3.4)' \quad \rho^{-1}t * (C_{ikmn}W_{mn})_{,k}(\mathbf{x}, t) = 0 \quad \text{on } \partial B_{\mathcal{U}} \times [0, \infty),$$

$$C_{ijmn}W_{mn}n_j = 0 \quad \text{on } \partial B_{\mathcal{F}} \times [0, \infty).$$

Moreover, (a), (3.3)' and (3.4)' imply that

$$(b) \quad s_{ij}(\mathbf{x}, 0) = 0, \quad \dot{s}_{ij}(\mathbf{x}, 0) = 0, \quad \mathbf{x} \in B$$

and

$$(c) \quad s_{ik,k}(\mathbf{x}, t) = 0 \quad \text{on} \quad \partial B_U \times [0, \infty),$$

$$(d) \quad s_{ij}n_j = 0 \quad \text{on} \quad \partial B_F \times [0, \infty).$$

Multiply both sides of Eq. (3.2)' by \dot{s}_{ij} and integrate over B , to obtain

$$\int_B [(\rho^{-1}s_{ik,k})_{,j}] \dot{s}_{ij} dB = \int_B \ddot{W}_{ij} \dot{s}_{ij} dB.$$

Hence, by integration by parts, we get

$$\int_B \left\{ [(\rho^{-1}s_{ik,k}) \dot{s}_{ij}]_{,j} - (\rho^{-1}s_{ik,k}) \dot{s}_{ij,j} \right\} dB = \int_B \ddot{W}_{ij} \dot{s}_{ij} dB$$

or, by use of the divergence theorem,

$$\int_{\partial B} (\rho^{-1}s_{ik,k}) \dot{s}_{ij} n_j dA - \int_B [(\rho^{-1}s_{ik,k}) \dot{s}_{ij,j}] dB = \int_B \ddot{W}_{ij} \dot{s}_{ij} dB.$$

By (c) and (d), we obtain

$$- \int_B [(\rho^{-1}s_{ik,k}) \dot{s}_{ij,j}] dB = \int_B \ddot{W}_{ij} \dot{s}_{ij} dB$$

or by (a)

$$\frac{1}{2} \frac{\partial}{\partial t} \int_B [(\rho^{-1}s_{ik,k}) \dot{s}_{ij,j} + C_{ijmn} \dot{W}_{ij} \dot{W}_{mn}] dB = 0,$$

and after integration with respect to time and using the initial conditions (3.3)' and (b), we get

$$(3.5) \quad \int_B [(\rho^{-1}s_{ik,k}) s_{ij,j} + C_{ijmn} \dot{W}_{ij} \dot{W}_{mn}] dB = 0.$$

Hence

$$(e) \quad s_{ij,j} = 0$$

and

$$(f) \quad \dot{W}_{ij} + \dot{W}_{ji} = 0.$$

Insert (e) into (3.2)' to get

$$(g) \quad 0 = \ddot{W}_{ij} \quad \forall \quad (\mathbf{x}, t) \in B \times [0, \infty).$$

Integrating the last equation twice and using the initial conditions (3.3)' we obtain the result

$$(h) \quad W_{ij} = 0 \quad \forall \quad (\mathbf{x}, t) \in B \times [0, \infty).$$

This completes the proof of the uniqueness theorem. \square

Note that the uniqueness theorem for a pure stress initial-boundary value problem of elastodynamics in which the elasticity tensor is positive definite and the density is positive was presented in [5], while the uniqueness theorem for a pure stress initial-boundary value problem of incompressible isotropic elastodynamics was given in [9].

4. Remarks

4.1.

Let us, in addition to the fields introduced in Sec. 2, define the elastic rotation vector field

$$(4.1) \quad \omega_k = \frac{1}{2} \varepsilon_{kab} w_{ab}^E$$

and elastic rotation tensor field

$$(4.2) \quad o_{mk} = \frac{1}{2} (w_{mk}^E - w_{km}^E).$$

Also, define the elastic bend-twist tensor as

$$(4.3) \quad \kappa_{mk} = \omega_{k,m}.$$

With these definitions we find that

$$o_{mk} = \frac{1}{2} (o_{mk} - o_{km})$$

or

$$o_{mk} = \frac{1}{2} (\delta_{ma} \delta_{kb} - \delta_{mb} \delta_{ka}) o_{ab}$$

or

$$o_{mk} = \frac{1}{2} \varepsilon_{mkq} \varepsilon_{qab} o_{ab}.$$

Hence

$$o_{mk} = \varepsilon_{mkq} \omega_q$$

and, by (4.3)

$$(4.4) \quad o_{mk,j} = \varepsilon_{mkq} \kappa_{jq}.$$

Therefore, Eq. (1.5)' which, by definitions (1.13) and (4.2) can be written as

$$(4.5) \quad \varepsilon_{ijm} (e_{mk} + o_{mk})_{,j} = \alpha_{ik},$$

takes the form

$$(4.6) \quad \varepsilon_{ijm} (e_{mk,j} + \varepsilon_{mkq} \kappa_{jq}) = \alpha_{ik}$$

and this is an equation identical with Eq.(2.11)₁ in [4].

4.2.

By taking symmetric part of the distortion problem (3.1) – (3.4), we arrive at the pure stress problem of elastodynamics with continuously distributed defects discussed in [4] (cf. THEOREM 3.3 in [4]).

4.3.

If a solution of the pure stress problem discussed in 4.2. is available, then the skew part of the distortion, *i.e.* a solution of the problem obtained by taking skew part of the problem (3.1) – (3.4), can be easily obtained.

5. Conclusions

1. A pure distortion initial-boundary value problem of linear elastodynamics with continuously distributed defects has been formulated, and a uniqueness theorem for the problem has been proved.

2. By a symmetrization, the problem and uniqueness theorem reduce to those of a pure stress formulation of elastodynamics with continuously distributed defects, cf. [4].

3. By defining the elastic rotation fields in terms of the distortion tensor, a dislocation density formula from [4] has been recovered.

Appendix

To show that the integral condition (1.2) implies the local equation (1.3), Stokes' theorem is used. The proof is due to LANDAU and LIFSHITZ [2]. First, we note that for an arbitrary vector \mathbf{a} we have

$$(A.1) \quad \oint_L a_i n_i dl = \int_{S_L} \varepsilon_{imn} a_{n,m} n_i dS,$$

where S_L is a surface that spans the contour L . Substituting w_{ik} instead of a_i into (A.1) we get

$$(A.2) \quad \oint_L w_{ik} n_i dl = \int_{S_L} \varepsilon_{imn} w_{nk,m} n_i dS.$$

Next, we note that a constant vector $\tilde{\mathbf{b}}$ may be represented by an integral involving the two-dimensional delta function

$$(A.3) \quad \tilde{b}_k = \int_{S_L} \tau_i \tilde{b}_k \delta(\xi) n_i dS,$$

where ξ is the two-dimensional radius vector taken from the axis of dislocation in the plane perpendicular to the vector $\boldsymbol{\tau}$ at the point considered, cf. Fig. 1. Substituting (A.2) and (A.3) into (1.2) we get

$$(A.4) \quad \int_{S_L} \varepsilon_{imn} w_{nk,m} n_i dS = - \int_{S_L} \tau_i \tilde{b}_k \delta(\xi) n_i dS.$$

Since the contour L is arbitrary, from (A.4) we obtain (1.3). This completes the proof of implication (1.2) \Rightarrow (1.3).

References

1. A. M. KOSEVICH, *Equation of motion of a dislocation*, Zh. E. T. F., **43**, 637–648, 1962.
2. L. D. LANDAU and E. M. LIFSHITZ, *Teoriya uprugosti*, Izd. Nauka Glavn. Red. Fiz.-Mat. Literatry, 3rd edition, Moskva 1965; also English translation: *Theory of elasticity*, Vol. 7 of *Course of Theoretical Physics*, Pergamon Press, Oxford 1970.
3. A. M. KOSEVICH, *Crystal dislocations and the theory of elasticity*, [in:] F.R.N. Nabarro [Ed.], *Dislocation in solids*, Vol. 1, North Holland, Amsterdam 1979.
4. J. IGNACZAK and C. R. A. RAO, *Stress characterization of elastodynamics with continuously distributed defects*, J. Elasticity, **30**, 219–250, 1993.
5. J. IGNACZAK, *Direct determination of stresses from the stress equations of motion in elasticity*, Arch. Mech. Stos., **11**, 671–678, 1959.

6. J. IGNACZAK, *A completeness problem for the stress equation of motion in the linear theory of elasticity*, Arch. Mech.Stos., **15**, 225–234, 1963.
7. I. S. SOKOLNIKOFF, *Mathematical theory of elasticity*, Second Edition, New York-Toronto-London 1956.
8. W. NOWACKI, *Theory of Elasticity* [in Polish], [in:] Mechanika techniczna t. IV Sprężystość [in Polish], [Ed.] M. Sokołowski, PWN, Warszawa 1978.
9. R. WOJNAR, *Uniqueness theorem for stress equations of isochoric motions of linear elasticity*, Arch. Mech., **26**, 747–750, 1974.

Received February 11, 1998; new version August 24, 1998.
